

P E T I T I O N

Commissioner for Patents
Alexandria, VA 22313

Your Petitioner, CHADRON D. MOFFITT, a citizen of the United States and a resident of the State of Iowa, whose post office address is 25833 Walleye Drive, Spirit Lake, Iowa 51360, prays that Letters Patent may be granted to him for the improvement in

A BLADE ATTACHMENT FOR AN ALL-TERRAIN VEHICLE

as set forth in the following specification.

BACKGROUND OF THE INVENTION

1. FIELD OF THE INVENTION

This invention relates to a blade attachment for an off-road vehicle such as an all-terrain vehicle (ATV) and more particularly to a blade attachment for an ATV wherein the angle of the blade may be conveniently selectively changed by means of an electric motor driven winch which is powered by the ATV electrical system.

2. DESCRIPTION OF THE RELATED ART

The assignee of this invention has manufactured straight and V-blades for ATVs for many years. The blades may be used to plow snow, dirt, etc. The prior art blades have been raised and lowered with respect to the ATV by lift handles, electric actuators, electric winches, etc. In assignee's prior art straight blade, the blade is selectively pivotally attached, about a vertical axis, to the forward end of a push tube assembly which is pivotally connected at its rearward end, about a horizontal axis, to the ATV. The blade is pivotally connected to the push tube assembly so that the blade may be

angled left, angled right or positioned in a straight position. When the operator of the
ATV desires to change the angle of the blade, the blade must be raised from the ground
with the operator then being required to dismount the ATV, unlock the blade, manually
pivotaly move the blade to the desired position, and then lock the blade in that position.
Similar prior art structures have also been used by other manufacturers of blade
attachments for ATVs. Various types of pivoting blade attachments are illustrated in
U.S. Patent Nos. 5,088,215; 4,615,130; and RE37,628. In each of the blades of the
previously identified patents, the operator must leave the ATV and remove or move a
locking pin, manually pivot the blade to the desired position, and then move the locking
pin to its locked position.

The requirement of the operator to dismount from the ATV and make the blade
adjustment is inconvenient in those plowing or grading operations where the angle of
the blade on the ATV must be frequently changed.

SUMMARY OF THE INVENTION

A blade attachment for an off-road vehicle such as an all-terrain vehicle (ATV) is
described with the ATV having a forward end, a rearward end, a right side, a left side,
and an underside. A mounting frame or push tube assembly is positioned beneath the
forward end of the ATV and has its rearward end pivotally connected, about a horizontal
axis, to the ATV. The mounting frame extends forwardly from its rearward end so that
its forward end is positioned forwardly of the forward end of the ATV. The forward end
of the mounting frame is selectively movable between raised and lowered positions by
any conventional means such as a lift handle, winch, linear actuator, etc. A first plate is

secured to the forward end of the mounting frame and has a hinge plate selectively
1 pivotally movably positioned thereon about a vertical axis with the hinge plate having a
forward end and a rearward end. The hinge plate has a blade position lever opening
formed therein. The hinge plate also has a plurality of spaced-apart notches formed in
5 its rearward end. The blade is secured to the hinge plate in conventional fashion so as
to be positioned forwardly thereof. A blade position lever is selectively pivotally movably
mounted on a blade position lever bracket which is operatively secured to the hinge
plate with the lower end of the lever extending downwardly through one of the notches
10 in the hinge plate and through the blade position lever opening formed in the first plate.
The blade position lever is selectively movably between locked and unlocked positions
and is normally yieldably maintained in its locked position. An electrically driven winch
mechanism is operatively mounted on the mounting frame and is operatively connected
to the hinge plate for selectively moving the hinge plate and the blade to various angular
15 positions with respect to the mounting frame and the ATV when the blade position lever
is in its unlocked position. The blade position lever is automatically moved to its
unlocked position by a linkage which operatively engages the underside of the ATV
when the forward end of the mounting frame and blade have been moved upwardly to a
predetermined position. The blade position lever returns to its locked position when the
20 forward end of the mounting frame and blade have been lowered a predetermined
distance from its raised position.

It is therefore a principal object of the invention to provide an improved blade
attachment for an all-terrain vehicle.

1 A further object of the invention is to provide a pivoting blade attachment for an
all-terrain vehicle with the blade being able to be pivoted by an electric winch
mechanism when the blade has been raised to its uppermost position.

5 A further object of the invention is to provide a pivoting blade attachment for an
ATV or off-road vehicle which enables the blade to be pivoted to various angular
positions by an electric winch means.

10 Yet another object of the invention is to provide an electrically operated winch
which selectively angles a blade on an ATV without the necessity of the operator of the
ATV dismounting from the ATV and manually pivoting the blade.

15 Yet another object of the invention is to provide a pivoting blade attachment for
an ATV or off-road vehicle which enables the blade to be pivoted to various angular
positions by an electric winch means which is operatively connected to the blade by a
"slip-clutch" means so that the blade is hand-adjustably angled at any time.

20 These and other objects will be apparent to those skilled in the art.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a perspective view of an ATV having a blade mounted thereon;

25 Figure 2 is an exploded perspective view of the means for mounting the blade on
the ATV and the means for pivotally moving the blade to various positions with respect
to the ATV;

Figure 3 is a perspective view of the means for mounting the blade on the ATV
and the means for pivotally moving the blade to various positions with respect to the
ATV;

Figure 4 is a partial side view illustrating the means by which the blade position lever is automatically unlocked as the blade is moved upwardly with respect to the ATV;

Figure 5 is a view similar to Figure 3 but which shows the mechanism in somewhat enlarged detail;

Figure 6 is a partial side view similar to Figure 5 except that the linkage has moved the blade position lever to its unlocked position;

Figure 7 is a top elevational view of the mechanism for unlocking the blade position lever;

Figure 8 is a top view of the means for moving the blade to various positions; and

Figure 9 is a partial exploded perspective view of the invention herein.

DESCRIPTION OF THE PREFERRED EMBODIMENT

The numeral 10 refers generally to an off-road vehicle such as an all-terrain vehicle (ATV), which may be 2-wheel drive or 4-wheel drive. ATV 10 includes a forward end 12, rearward end 14, a left side 16, and a right side 18. The blade attachment of this invention is referred to generally by the reference numeral 20. Attachment 20 includes a push tube assembly 22 comprising push tubes 24, 26 which have their rearward ends pivotally secured to the frame of the ATV by a pin or pins (not shown) in conventional fashion. Support plate 28 is welded or otherwise secured to the forward ends of push tubes 24, 26 and has its forward end 30 positioned forwardly of the forward ends of push tubes 24, 26. Threaded bolt or stud 32 extends upwardly from the forward end of plate 28, as seen in Figure 2. Plate 28 has a longitudinally extending blade position lever slot or opening 34 formed therein forwardly of the rearward end

thereof. Plate 28 also has an opening 36 formed therein rearwardly of slot 34 which is adapted to receive bolt 38 extending upwardly therethrough which is adapted to threadably receive nut 130.

The reference numeral 40 refers to a hinge plate which is positioned above plate 28 including a base portion 42 and upstanding sides 44, 46. Hinge plate 40 includes an opening 48 formed in base portion 42 which is adapted to receive bolt 32 extending upwardly therethrough to enable hinge plate 40 to pivotally move with respect to plate 28. The rearward end of base portion 42 has a plurality of slots or notches formed therein which will be referred to as slots 50, 52 and 54. Any number of slots may be utilized but it is preferred that there be at least a center slot 52, a left slot 50 and a right slot 54.

Plates 56, 58 and 60 are positioned between support plate 28 and base portion 42 of plate 40 as will now be described. Plate 56 will be referred to as a bottom plate and includes an arcuate peripheral surface 62 extending from its forward end 64 which includes a cutout portion 66. Bottom plate 56 has an opening 68 formed therein which receives the bolt 32 extending upwardly therethrough. Plate 58 will be referred to as a mid-plate which includes an arcuate peripheral surface 70 extending from forward end 72. Mid plate 58 has an opening 74 formed therein which receives the bolt 32 extending upwardly therethrough. Plate 60 will be referred to as a top plate which includes an arcuate peripheral surface 76 extending from forward end 78. Plate 60 includes an opening 82 through which bolt 32 extends. As seen, the forward end 78 of top plate 60 has an upwardly extending lip or shoulder 80 which engages the forward

1 end of base portion 42 of hinge plate 40 so that rotation of top plate 60 will cause hinge
plate 40 to be pivoted or rotated therewith when in its unlocked position, as will be
described in greater detail hereinafter. The plates 56, 58 and 60 are welded together so
that they move as a unit.

5 Bolt 38 extends upwardly through opening 36 in plate 28 and through opening 84
in blade position lever bracket 86. Eyebolt 92 has its forward "eye" portion positioned
beneath bracket 86, as seen in the drawings. Bolt 38 extends through the "eye" portion
of eyebolt 92. Bracket 86 has an upstanding ear 94 secured thereto which has an
opening 96 formed therein adapted to receive a bolt 98 therein. Blade position lever
10 100 has oppositely extending tabs or ears 102 and 104 secured thereto. Tab 102 has
an elongated slot 103 formed therein while tab 104 has an opening 105 formed therein.
Blade position lever 100 has an opening 107 formed therein above tabs 102 and 104.
The lower end 106 of lever 100 extends downwardly through a slot formed in the bottom
15 portion of bracket 86. Lever 100 is pivotally secured to ear 94 and bracket 86 by bolt 98
which extends through opening 107 in lever 100. One end of spring 110 is connected to
tab 104 with the other end thereof being connected to bracket 112 secured to the
forward end of bracket 86 (Figure 5).

20 Plate 114 is secured to tubes 24 and 26 by U-bolts 116 and 118, respectively.
Plate 114 has an upstanding ear 120 secured to the forward end thereof which has a
plurality of openings 122 formed therein adapted to have bolt 124 extending
therethrough which receives nut 126. Adjustment tube 128 is secured to plate 114 by
welding or the like. The rearward end of eyebolt 92 is adjustably received within the
25

1 forward end of tube 128. Adjustment nut 130 is threadably mounted on the eyebolt 92
forwardly of the forward end of tube 128 to provide a "fine" adjustment of the plate 114
on the mounting frame 22 when U-bolts 116 and 118 are loosened. Once plate 114 is
adjusted, U-bolts 116 and 118 are tightened. Links or bars 134 and 136 are selectively
5 vertically and horizontally secured to ear 120 by pin 124. The forward ends of links 134
and 136 are slidably connected to tab 102 of blade position lever 100 by bolt 137
extending through slot 103 and maintained therein by nut 137'. The rearward ends of
links 134 and 136 have an actuator 140 selectively vertically and horizontally secured
thereto by bolt 142.

10 An electric winch 144 including a fractional horsepower electric motor 146, driven
by the vehicle electrical system, and a winch drum 148 is secured to plate 114, as seen
in the drawings. A skid plate 150 is positioned below the winch 144 for protecting the
winch 144 from damage. Winch drum 146 has a few wraps of winch cable 152
15 extending therearound to define cable portions 154 and 156. The cable portions 154
and 156 of 152 extend forwardly from drum 146 through slot 158 formed in plate 114
and are crossed, as seen in Figure 7. The cable portions 154 and 156 extend around a
portion of the arcuate periphery 70 of mid-plate 58 between plates 56 and 60. The ends
of cable portions 154 and 156 have eyes 158 and 160 attached thereto, respectively, as
20 seen in Figure 7. Eyes 158 and 160 are connected together by spring 162 which is
positioned forwardly of forward end 72 of plate 58 and within cutout area 66 of plate 58.
Spring 162 maintains cable portions 154 and 156 in yieldably frictional engagement with
plate 58 and drum 146 so that movement of the cable portions 154 and 156 by the
25

1 electric motor 146 will cause plate 58 to rotate about bolt 32. Since plates 56, 58 and
60 are welded together, rotation of plate 58 will cause plates 56 and 60 to also rotate.
Rotation of plate 60 will cause hinge plate 40 to pivot about bolt 32 due to the
engagement of lip 80 with the forward end of hinge plate 40.

5 Bracket 86 has a slot 169 and holes 170 to receive a winch hook or manual lift
handle or electric blade lift components to raise and lower the forward end of push tube
assembly 22 and blade 168. Blade 168 is connected to hinge plate 40 in conventional
fashion whereby blade 168 moves with hinge plate 40 about the vertical axis defined by
bolt 32.

10 When it is desired to change the angle of the blade 168 with respect to the off-
road vehicle such as an ATV 10, the blade 168 is raised from ground engagement by
the lift handle, linear actuator, winch, etc., which causes the push tube assembly 22 to
pivotally move upwardly about its rearward end. As the push tube assembly 22 and the
15 blade 168 are raised with respect to the ATV 10, the selectively adjustable actuator 140
will come into contact with a selectable portion of the underside of the ATV 10, as
illustrated in Figure 5. Continued upward movement of the push tube assembly 22 and
the blade 168 will cause the links 134 and 136 to move downwardly, as indicated by the
arrows in Figure 4, due to the pivotal connection of the links 134 and 136 to the plate
20 114. As the links 134 and 136 move downwardly, the links 134 and 136 exert an
upward force on the lever 100 which causes the lever 100 to pivot about bolt 98 which
causes the lower end of the lever 100 to move rearwardly out of engagement with the
notches or slots 50, 52 and 54, depending upon which slot it is positioned in, so that

1 hinge plate 40 and the blade 168 are not locked into position. At that time, the winch
144 is actuated in the desired direction so that end cable portion 154 is moved
rearwardly while the other cable portion 156 is moved forwardly or vice versa.
Movement of the cable portions 154 and 156 by the winch 144 causes the plates 56, 58
5 and 60 to be rotated which causes the hinge plate 40 to also be rotated or pivotally
moved with respect to the push tube assembly 22 about the bolt 32. The spring 162
exerts tension on the cable portions 154 and 156 to maintain the cable portions 154 and
156 in frictional engagement with the periphery of plate 58 and drum 146. The tension
on the cable portions 154 and 156 may also be adjusted by loosening the U-bolts 116
10 and 118 and then threadably rotating nut 130 on eyebolt 92 so that plate 114 is moved
with respect to the push tube assembly 22. When the plate 114 has been moved to a
position wherein the proper tension of cable portions 154 and 156 is achieved, the U-
bolts 116 and 118 are then tightened.

15 When the blade has been moved to the desired angle, the push tube assembly
22 and the blade 168 are then lowered somewhat so that the actuator 140 moves out of
engagement with the underside of the ATV so that spring 110 urges the lower end of
lever 100 towards the rearward end of the hinge plate 40 and the notches or slots
20 formed therein. The winch 144 may then be actuated to properly align the lower end of
the lever 100 with the desired slot 50, 52 or 54 so that the lever 100 will lock the hinge
plate and the blade into its desired angular position with respect to the ATV.

25 The wrapping of a few loops of the winch cable around the drum of the winch 144
provides a "slip clutch" attachment of the cable to the winch drum so that if the lever 100

is not perfectly received within one of the slots 50, 52 and 54, the blade, when striking
an obstruction, will not impart a direct stress onto the winch. Further, should the winch
144 become inoperative for one reason or another, the operator may manually pivot the
blade 168 since the cable may slip on the drum without causing the drum to rotate
which would be resisted by the gear drive mechanism of the winch, therefore also
adding an additional protection to the rotating winch assembly should the blade come
into contact with an obstruction causing the blade to rotate until locked without causing
damage to the winch assembly.

It can therefore be seen that a novel apparatus has been provided which enables
a blade to be pivotally moved between its various angular positions with respect to the
ATV without the need of the operator dismounting from the ATV.

Thus it can be seen that the invention accomplishes at least all of its stated
objectives.